

primus®

GET AHEAD IN LAUNDRY



PC20 | PC30 | PC40 | PC60

HARDMOUNT WASHER-EXTRACTORS



PATENTED WATER GUARDIAN
Detects leaking valves



EXTRA LARGE DOOR OPENING
For easy loading and unloading



IMPROVED DURABILITY
for your peace of mind with a
3-year warranty

FEATURES & BENEFITS

FEATURES

- Rigid mounted, normal spin, 200G factor
- Stainless Steel drum and tub
- High capacity water inlets
- Large drain valve
- Large door opening for easy loading and unloading
- Industry-leading flexible water level settings
- patented Fill and Drain leak detection saves water
- Lighter, consumption-optimized frame
- Designed to reduce sound and vibration levels

PLATFORM: XCONTROL FLEX

- Available with XControl FLEX for Vend
- Full color, touch screen display
- Clear step-by-step instructions available in 34 languages
- Machine programming & performance data accessible through cloud. Remotely access to live machine data on mobile device
- VEND:
 - 15 easy-to-use washer cycle modifier
 - Count up timer
 - Over-the-air updates

SPECIFICATIONS

TYPE	PC20	PC30	PC40	PC60
Control Option	XControl FLEX	XControl FLEX	XControl FLEX	XControl FLEX
Capacity - [kg (lb)]	9 (20)	14 (30)	18 (40)	27 (60)
Overall Width - [mm (in)]	660 (26)	737 (29)	778 (30.6)	865 (34.1)
Overall Depth - [mm (in)]	784 (30.9)	896 (35.3)	1073 (42.3)	1135 (44.7)
Overall Height - [mm (in)]	1120 (44.1)	1196 (47.1)	1252 (49.3)	1295 (51)
Cylinder Diameter - [mm (in)]	533 (21)	610 (24)	668 (26.3)	762 (30)
Cylinder Depth - [mm (in)]	350 (13.8)	406 (16)	516 (20.3)	559 (22)
Cylinder Volume - [l (cu. ft.)]	79.3 (2.8)	119 (4.2)	178 (6.3)	255 (9.0)
Door Opening Size - [mm (in)]	295 (11.6)	363 (14.3)	414 (16.3)	414 (16.3)
Door Bottom to Floor - [mm (in)]	366 (14.4)	356 (14)	371 (14.6)	378 (14.9)
Water Inlet Connection - [mm(in)]	2 @ 19 (0.75)	2 @ 19 (0.75)	2 @ 19 (0.75)	4 @ 19 (0.75)
Drain Diameter - [mm (in)]	1 @ 76 (3)	1 @ 76 (3)	1 @ 76 (3)	1 @ 76 (3)
Drain Height to Floor - [mm (in)]	99 (3.9)	109 (4.3)	114 (4.5)	124 (4.9)
Total #of Speeds	9	9	9	9
CYLINDER SPEEDS - [RPM(G-FORCE)] Ultra High	819(200)	766(200)	733(200)	686(200)
VOLTAGEWIRES/ CIRCUIT BREAKER -				
FLA120/60/1	15.IX	N/A	20 - 15	N/A
200-208/220-240/50/60/3/1/3	15 - 4 (1 Ph) 15 - 3 (3 Ph)	15 - 7 (1 Ph) 15 - 4 (3 Ph)	15 - 7 (1 Ph) 15 - 4 (3 Ph)	15 - 11 (1 Ph) 15 - 7 (3 Ph)
200-208/220- 240/50/60/3/3	30 - 22	30-22	50 - 41	50 - 41
440-480/50/60/3/3	15 - 2	15 - 3	15 - 3	15 - 4
380-415/50/60/3/3	15 - 4	15 - 4	15 - 5	15 - 6
SHIPPING DIMENSIONS AP- PROX. - [mm (in)]				
Width	711 (28)	800 (31.5)	826 (32.5)	953 (37.5)
Depth	859 (33.8)	937 (38.3)	1105 (43.5)	1191 (46.9)
Height	1255 (49.4)	1303 (51.3)	1361 (53.6)	1430 (56.3)
Motor Power Consumption - [kW (HP)]	0.75 (1)	0.75 (1)	1.5 (2)	2.25 (3)
Net Weight - [kg (lb)]	154 (340)	197 (435)	249 (550)	308 (680)
Shipping Weight - [kg (lb)]	172 (380)	215 (475)	268 (590)	327 (720)
Slat Crate Shipping Weight - [kg (lb)]	209 (460)	263 (580)	308 (680)	381 (840)

DIMENSIONS

	A	B	C	D
PC20	660	784	1120	365
PC30	737	896	1196	365
PC40	778	1073	1252	368
PC60	865	1191	1295	379
	width	depth	height	door bottom to floor

